

Product information Mechanical risks

uvex phynomic airLite B ESD//60078



Description

A noticeable difference in wearer comfort in Cut Level B: combination of high sensitivity and tactile feel, lightness. The phynomic airLite B ESD is certified according to the DIN EN 16350:2014 (1149-2) standard and is also tested based on the DIN EN 1149-1. Therefore it is perfectly applicable in ESD areas and areas exposed to explosion hazards. You will be equipped for the future with the uvex phynomic airLite B ESD thanks to its touchscreen compatibility for use on all screens, tablets and mobile phones. It is free from accelerators, health protection and skin compatibility dermatologically approved (proDERM®).

Characteristics

- 18 Gauge Liner
- anti-static in accordance with EN 16350
- outstanding wearer comfort
- Ergonomic fit
- Flexibility and secure grip
- free from catalysts
- suitable for use with touchscreens
- good breathability
- exceptional dexterity right to the fingertips
- ultra-lightweight
- certified according to Öko-Tex Standard 100

Applications

- Work on touchscreen
- ESD areas
- precision assembly work
- For work in antistatic areas
- inspection/maintenance
- precision work
- handling of sharp objects for: assembly, sorting, packaging

EN 388:2016



3X32B



pure standard



MADE IN GERMANY

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG
 Elso-Klöver-Str. 6
 21337 Lüneburg
 Postfach 24 47 · 21314 Lüneburg
 GERMANY
 Tel.: +49 4131 9502-0
 Fax: +49 4131 84338
 Email: gloves@uvex.de
 Website: uvex-safety.de

| | |
|--------------|---|
| Product name | uvex phynomic airLite B ESD |
| EN | 388:2016 (3 X 3 2 B) |
| Sizes | 6, 7, 8, 9, 10, 11, 12 |
| Construction | palm and fingertips coated, knitted cuff |
| Basic glove | Dyneema®Diamond Technology, Polyamid, Elastan, Carbon |
| Coating | Aqua-Polymer Beschichtung airLite |
| Thickness | |
| Colour | blue/anthracite |
| Resistance | for dry areas and slightly damp/oily working conditions |
| Product code | 60078 |