


Product Datasheet model uvex i-5 9183 265

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Product
characteristics**

- soft, flexible nose pad for maximum comfort and a non-slip fit
- x-tended eyeshield provides additional protection from flying particles, dust and dirt
- x-tended sideshield for increased side protection
- 3-position side arm inclination adapts easily to any facial shape
- soft, extendable x-twist side arm technology offers adaptable, pressure-free comfort and a stable, non-slip fit
- soft ear pieces (uvex duo Component technology) prevent pressure points and ensure a non-slip fit
- with proven uvex supravision lens coating technology

Technical details	
Frame	Front piece/Temple
Material	TPU/TPE
Features	multilevel inclination, individual adjustable
Colour	blue, anthracite
	Marking
Manufacturer's ID code	W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temp.	T
Conformity symbol	CE
Lens	
Material	PC
Thickness	1,91 mm
Coating	uvex supravision excellence
Colour	clear
UV-Schutz	UV 400

	Marking
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W 1
Optical class	F (45 m/s)
Low-energy impact Resistance to high speed particles at extremes of temp.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	
Miscellaneous	
Weight	29 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170
PPE Category	Category II