


**Product Datasheet model super f OTG 9169 261**

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>• overspecs for prescription wearers</li><li>• unrestricted peripheral vision</li><li>• side arms graduate to soft, flexible material for added comfort and grip</li></ul>
<b>Technical details</b>	
<b>Frame</b>	
Material	<b>Front piece</b> PA
Colour	black
Material	<b>Temple</b> PA/TPE
Colour	black, white

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temp.	T
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	uvex supravision excellence
Colour	clear
UV protection	UV 400
<b>Filter</b>	
Filter	<b>Marking</b> 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	

**Miscellaneous**

Weight	38 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170
PSA Category	Category II